



6262 Katella Avenue
Cypress, CA 90630, USA
Tel: 714 548-3999
Fax: 714 548-3991
www.Shercon.com

PS Series

Vinyl Caps

Purpose

Vinyl Caps are designed to mask plain and threaded studs, tube ends and even slotted holes; they will mask off the stud and allow finishing up to it. They are also widely used for protection during transportation

How the product is used

The cap is applied by being pushed over the stud. It is removed by being pulled off. It can be used as a plug by being inserted into threaded or plain holes. However, on holes we would recommend a plug such as the GN series of plugs or the PP series of pull plugs. If the cap is used as a plug it can be pushed into place using a rounded end rod or dowel.

The outside diameter of this cap may vary in size due to the manufacturing process.

Recommended for

Plating, Anodizing, Spray painting, Protection during transportation

Temperature range

Maximum temperature 350°F (177°C)

Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

Design features

- **Flexible** - The cap is flexible so it can fit a range of different diameters
- **Tight Fit** - Caps are flexible enough to stretch over tabs and form a tight fit
- **Lengths** - Many of the diameters are available in different lengths
- **Reusable** - The plugs are reusable depending on the application
- **Color coded** - The caps are color coded to ease identification and sorting

Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.