



6262 Katella Avenue  
Cypress, CA 90630, USA  
Tel: 714 548-3999  
Fax: 714 548-3991  
www.Shercon.com



# E-Z Peel™ Discs

## Specification

Description	Value	ASTM Test Method
Total thickness	7.5 Mil (0.19 mm)	D-3652
Color	Cream	
Adhesive	Rubber	
Elongation at break	10%	D-3759
Tensile strength	26lb / inch (455N / 100mm)	D-3759
Adhesion to steel	28 oz / inch (0.31Kg / cm)	D-3330
Temperature range	-60°F to 200°F (-50°C to 93°C)	
Storage conditions	Keep in dry conditions	
Removability	Good to excellent	
Tolerances	Discs can be cut to $\pm 0.005''$ ( $\pm 0.127\text{mm}$ )	

## General Description

E-Z Peel™ Discs are manufactured a high temperature, pressure sensitive masking tape designed for clean removal. It has a fine structured smooth crepe backing with high strength. It provides both resistance to paint flaking and a clean well-defined masking line. Discs are provided on a liner, which is wound on a core.

## Recommended for

Spray painting.

## Availability

In addition to these discs this tape is also available as pre-cut rectangles, squares, and donuts. It is also available as die cut shapes

## Storage Conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received. Rolls of discs or die cuts should be stored on end.