



6262 Katella Avenue
Cypress, CA 90630, USA
Tel: 714 548-3999
Fax: 714 548-3991
www.Shercon.com



Kwicky Dot™ Discs

Specification

Description	Value	ASTM Test Method
Total thickness	7.5 Mil (0.19 mm)	D-3652
Color	Cream	
Adhesive	Acrylic	
Tensile strength	26lb / inch (455N / 100mm)	
Elongation at break	10%	D-3759
Adhesion to steel	28 oz / inch (0.31Kg / cm)	D-3330
Temperature range	-60°F to 300°F (-50°C to 149°C)	
Storage conditions	Keep in dry conditions	
Removability	Good to excellent	
Tolerances	Discs can be cut to $\pm 0.005''$ ($\pm 0.127\text{mm}$)	

General Description

Kwicky Dot™ Discs are manufactured from KD11. KD11 is a high temperature, pressure sensitive masking tape designed for clean removal. It performs well in wet strip applications and can be stripped hot. It has a fine structured smooth crepe backing with high strength. It provides both resistance to paint flaking and a clean well-defined masking line. Discs are provided on a liner, which is wound on a core. Diameters between 3/16" and 1" are overlapped for rapid application

Recommended for

Spray painting.

Availability

In addition to these discs KD11 is available in roll form in a range of imperial and metric widths. This tape is also available as pre-cut rectangles, squares, and donuts. It is also available as die cut shapes.

Storage Conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received. Rolls of discs or die cuts should be stored on end.