



6262 Katella Avenue  
Cypress, CA 90630, USA  
Tel: 714 548-3999  
Fax: 714 548-3991  
www.Shercon.com

## HUP Series

# Hollow Ultrabake™ Plugs

## Purpose

Hollow Ultrabake™ Plugs are designed to plug plain and threaded holes; they will mask off the hole and allow finishing up to it.

## How the product is used

The hole can be a blind hole or a through hole.

The plug is tapered and is applied by pushing the smaller diameter into the hole. The plug is removed by pulling on the larger diameter.

This range of plugs is hollowed out making them lighter

## Recommended for

Powder coating, E-coating, Plating, Anodizing, Spray painting

## Temperature range

Maximum temperature 600°F (315°C)

## Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

## Design features

- **Tapered** - The plug is tapered and can be fitted into a range of different diameters
- **Flexibility** - The material is soft and conforming. This allows the plug to seal the hole
- **Hollow** - The plugs are hollow making them lighter and more conforming
- **Tapered Hollow** - The hollow section is tapered to ensure the plug does not trap liquid
- **Reusable** - The plugs are reusable depending on the application
- **Color coded** - The plugs are color coded to ease identification and sorting
- **Identification** - The Shercon name is on the product

## Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.