

6262 Katella Avenue Cypress, CA 90630, USA Tel: 714 548-3999 Fax: 714 548-3991 www.Shercon.com

## **HUP-H** Series

# Hollow Ultrabake<sup>™</sup> Plugs with Handles

#### Purpose

Hollow Ultrabake<sup>™</sup> Plugs with Handles are designed to plug plain and threaded holes; they will mask off the hole and allow finishing up to it.

#### How the product is used

The plug is tapered and is applied by using the handle to push the smaller diameter into the hole. The plug is removed by pulling on the handle.

The hole can be a blind hole or a through hole.

This range of plugs is hollowed out making them lighter.

#### **Recommended for**

Powder coating, E-coating, Plating, Anodizing, Spray painting

#### **Temperature range**

Maximum temperature 600°F (315°C)

#### Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

## **Design features**

- **Tapered** The plug is tapered and can be fitted into a range of different diameters
- Handle The plugs have a handle to ease and speed up insertion and removal
- Hollow The plugs are hollow making them lighter and more conforming
- Visible The handle can help an operator see the mask on the component and therefore speed up removal of masks

- Reusable The plugs are reusable depending on the application
- Color coded The plugs are color coded to ease identification and sorting
- Identification The Shercon name is on the product

### Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.