



6262 Katella Avenue
Cypress, CA 90630, USA
Tel: 714 548-3999
Fax: 714 548-3991
www.Shercon.com

UFP Series

Ultrabake™ Flangeless Plugs

Purpose

Ultrabake™ Flangeless Plugs are designed to plug threaded holes; they will mask off the hole and can cover a portion of the top thread of the hole to allow painting up to the threads.

How the product is used

The plug is applied by pushing the tapered ribbed end of the plug into the threaded hole. It can be “screwed” in, but the profile of the plug is not a thread. The plug can be used on plain bores, but on those, we would recommend the UP series of plugs or a pull plug such as the SPP series of pull plugs.

The plug is removed by pulling on the handle

Recommended for

Powder coating, E-coating, Plating, Anodizing, Spray painting

Temperature range

Maximum temperature 600°F (315°C)

Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

Design features

- **Tapered** - The plug is tapered for easy insertion and removal
- **Handle** - The plugs have a handle to ease and speed up insertion and removal
- **Visible** - The raised handle makes the plug easier to see on the component
- **Hollow** - The larger diameter plugs are hollow making them lighter and more conforming
- **Reusable** - The plugs are reusable depending on the application
- **Color coded** - The plugs are color coded to ease identification and sorting
- **Identification** - The Shercon name is on the product

Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.