



6262 Katella Avenue
Cypress, CA 90630, USA
Tel: 714 548-3999
Fax: 714 548-3991
www.Shercon.com

UMFP Series

Ultrabake™ Multi-Flanged Plugs

Purpose

Ultrabake™ Multi-Flanged Plugs are designed to mask plain and threaded holes; they will mask off the hole and will allow painting up to the hole.

How the product is used

The plug is applied by being pushed into the hole. The plug is tapered and as it is pushed into the hole the flanges or fins compress and bend to grip the side of the hole. One plug can fit a number of different hole diameters.

Recommended for

Powder coating, E-coating, Plating, Anodizing, Spray painting

Temperature range

Maximum temperature 600°F (315°C)

Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

Design features

- **Tapered** - The plug is tapered for easy insertion and removal
- **Reusable** - The plugs are reusable depending on the application
- **Flexible** - The fins on the plug are flexible so the plug can fit a range of holes
- **Color coded** - The plugs are color coded to ease identification and sorting
- **Handle** - The plugs have a handle to ease and speed up insertion and removal
- **Identification** - The Shercon name is on the product
- **Handle** - The handle area above the flanged diameter helps with removal
- **Visible** - The raised handle makes the plug easier to see on the component

Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.