



6262 Katella Avenue  
Cypress, CA 90630, USA  
Tel: 714 548-3999  
Fax: 714 548-3991  
www.Shercon.com



# Ultrabake™ Thread Mask

## Purpose

Ultrabake™ Thread Masks are designed to mask threaded holes; they will mask off the hole and the first thread of the hole.

## How the product is used

The plug is applied by being pushed into the threaded hole until the larger diameter is tight against the face of the thread to be masked. The plug is removed by pulling on the handle.

## Recommended for

Powder coating, E-coating, Plating, Anodizing, Spray painting

## Temperature range

Maximum temperature 600°F (315°C)

## Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

## Design features

- **Flanged** - The flanged area masks off the first thread of a threaded hole
- **Handle** - The handle area above the flanged diameter helps with insertion and removal
- **Sizes** - This series offers sizes specifically designed for metric threaded holes
- **Shallow** - The shallow design is ideal for blind holes and helps speed up the masking process
- **Long Series** - Long series masks have longer handles for hard to reach areas and a longer sealing area
- **Visible** - The handle area above the flanged diameter makes the plug easier to see on the component
- **Reusable** The plugs are reusable depending on the application
- **Color coded** - The plugs are color coded to ease identification and sorting
- **Identification** - The Shercon name is on the product

## Custom

Custom sizes and colors are available of this design.