



6262 Katella Avenue
Cypress, CA 90630, USA
Tel: 714 548-3999
Fax: 714 548-3991
www.Shercon.com

UVCP Series

Ultrabake™ Venting Cap Plugs

Purpose

Ultrabake™ Venting Cap Plugs are designed to mask plain and threaded studs or holes; there is a small nipple on the top of the mask which can easily be punctured or removed to form the small vent. The masks then mask off the hole or stud and allow trapped air to escape from inside the cap through the vent.

How the product is used

When used as a cap the cap is applied by being pushed over the stud, as the cap is pushed onto the stud the trapped air will escape from the inside of the cap allowing the operator to push the cap down into position. It can then be removed by being pulled off. When used as a plug the plug can be pushed into the hole and air will escape from the plug as the plug is pushed into position.

Recommended for

Powder coating, E-coating, Plating, Anodizing, Spray painting

Temperature range

Maximum temperature 600°F (315°C)

Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

Design features

- **Vented** - The cap plug is vented to allow trapped air to escape
- **Reusable** - The plugs are reusable depending on the application
- **Flexible** - The cap plug is flexible so it can fit over a series of different diameters
- **Color coded** - The plugs are color coded to ease identification and sorting
- **Identification** - The Shercon name is on the product

Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.