



6262 Katella Avenue
Cypress, CA 90630, USA
Tel: 714 548-3999
Fax: 714 548-3991
www.Shercon.com

UW Series

Ultrabake™ Washer Plugs

Purpose

Ultrabake™ Washer Plugs are designed to mask plain and threaded holes; they will mask off the hole and leave a circular grounding or earthing area around the hole.

How the product is used

The plug is applied by pushing a tapered end into the hole until the larger diameter rests against the face. These are a dual-purpose plug. On UW-M3 to UW-M12 one side of the plug is designed to fit the metric threaded hole, whilst the other side of the plug is designed to fit a standard metric clear hole.

One end of the plug can be used as a handle to insert and remove the plug.

Recommended for

Powder coating, E-coating, Plating, Anodizing, Spray painting

Temperature range

Maximum temperature 600°F (315°C)

Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

Design features

- **Tapered** - The plug is tapered for easy entry and removal
- **Handle** - The additional end makes the plug easy to insert and remove
- **Sizes** - This series offers sizes specifically designed for metric threaded holes
- **Visible** - The additional end makes the plug easier to see on the component
- **Labor Saving** - The step design eliminates the need for two-stage masking
- **Reusable** - The plugs are reusable depending on the application
- **Color coded** - The plugs are color coded to ease identification and sorting
- **Identification** - The Shercon name is on the product

Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.