



6262 Katella Avenue
Cypress, CA 90630, USA
Tel: 714 548-3999
Fax: 714 548-3991
www.Shercon.com

US Series

Ultrabake™ Sheeting

Purpose

To cover large areas. It can be die cut into shapes and can be used in conjunction with a double sided tape, to mask off large areas, or to simply provide a liner / protective layer on areas that will come into contact with heat.

How the product is used

The sheeting is provided in 36" * 36" (1296mm * 1296mm) square pieces in various thickness from 1/32" (0.79mm) to 1/2" (12.7mm). It can be die cut into shapes for gaskets, pads, strips, washers or seals. Please note, on the thicker materials, the sides may have a slight taper as the die will have a tendency to compress the material before it begins to cut it.

Recommended for

Powder coating, E-coating, Plating, Anodizing, Spray painting

Temperature range

Maximum temperature 600°F (315°C)

Storage conditions

Items should be stored in dry conditions at an ambient temperature of between 55°F (13°C) and 85°F (30°C). It is important to rotate stock and use the product in the order that it is received.

Design features

- **Flexible** - The sheeting is flexible so it can fit a range of different profiles
- **Smooth** - The sheeting is smooth, unlike silicone foam sheeting which has a texture
- **Reusable** - The sheeting is reusable depending on the application
- **Sizes** - The sheeting can be cut to your requirements
- **Shapes** - The sheeting can be die cut to the shape you require

Custom sizes and colors

Custom sizes are available of this design. Custom colors are available; however, they are subject to a minimum order quantity.